

seca mBCA 525

medical Body Composition Analyzer

new

- Measurement of fat, water, muscle and other body parameters in lying position.
- Perfect for mobile use at only 6.6 lbs with long-lasting rechargeable battery.
- Wi-Fi connection between measuring mat and monitor guarantees reliable data transmission.
- Easy-to-understand graphic presentation of measurement results on the touchscreen monitor.
- Internal storage for results of approximately 100,000 measurements.
- The only body composition analyzer designed for medical use and validated against the Four Compartment Model – the gold standard* for fat-free mass estimation.



* Study: Bomy-Westphal A, Schautz B, Later W, Kehayias JJ, Gallagher D. What makes a BIA equation unique? Validity of eight-electrode multifrequency BIA to estimate body composition in a healthy adult population. Eur J Clin Nutr 2013; 67: 14-21; doi:10.1038/ejcn.2012.160

seca mBCA 525 –

New development in lying measuring: mobile mBCA for medical body composition analysis.

The vital functions of immobile patients in particular have to be monitored at all times. The seca mBCA 525 was developed for just this application. Lightweight and compact, the device is equipped with its own Wi-Fi for immediate entry in available networks. The sophisticated technology delivers reliable and reproducible medical data and stores the results internally. The seca mBCA 525 is ideal for mobile use by Registered Dietitians treating bedridden patients or for use in intensive care in the hospital.

Technical Data

General

Dimensions (WxHxD)	9.9 x 10.3 x 9.1" / 252 x 262 x 230 mm
Weight	6.6 lbs / 3 kg
Display	7" touchscreen-display
Power supply	power adapter, rechargeable battery
Voltage	100 V–240 V
Power frequency	50 Hz–60 Hz
Interfaces	Wi-Fi, Ethernet, USB 2.0, seca 360° wireless technology
Compatible printers	laser printer and inkjet printer via PC software seca analytics 115

Bioelectrical Impedance Analysis

Measurement method	8-point Bioelectrical Impedance Analysis
Type of electrode	adhesive electrodes (PVC-free)
Measurement frequencies	1; 2; 5; 10; 50; 100; 200; 500 kHz
Measurements	Impedance (Z), Resistance (R), Reactance (Xc), Phase angle (φ)
Phase angle measurement range	0° to 20°
Measurement range Impedance	10 Ω to 1,000 Ω
Measurement segments	Right arm, left arm, right leg, left leg, right half of body, left half of body, torso
Measurement current	100 μA
Measurement time	30 seconds

Information

The patient monitor is equipped with seca 360° wireless technology and can receive data from the following devices:

- seca scales in seca 360° wireless system (weight)
- seca height measuring systems in seca 360° wireless system (height)
- seca measuring stations in seca 360° wireless system (weight and height)

Included with

Monitor, measuring mat, PC software seca analytics 115 (one workstation license), power adapter, electrode starter set

Accessories

seca 475 mobile stand, seca 432 carrying case

