

# EMR-validated column scale with 660 pounds capacity

**seca**  
Precision for health

## seca 703

- + Extremely robust, highly precise seca weighing technology with 660 pounds capacity
- + Non-tilting base made of heavy duty cast iron
- + Impact- and scratch-resistant powder coating
- + Wide range of functions: BMI, pre-TARE, HOLD, Auto-HOLD, mother+child function, three-step damping
- + Expandable to measuring station with an optional height measuring rod
- + Optional panda bear facilitates measuring and weighing of children
- + EMR-validated: transmit measured data directly to an electronic medical record system or printer



EMR

Image contains included measuring rod seca 220.

seca 703

## EMR-validated column scale with 660 pounds capacity



### Is not only highly resilient, but also ultra-precise

Stability conveys a secure feeling and inspires confidence in the measuring results and for the treating physician. That's why the seca 703 has a cast-iron undercarriage with a non-slip rubber pad. Even patients affected by obesity up to 660 lbs can be weighed safely and accurately. The fine graduation shows that the column scale is not only heavy-duty and durable, but also meets all requirements for accuracy.

### Prepared for every situation

For the calculation of the BMI, the height can be read and entered from a retrofittable measuring rod. In addition to BMI calculation, many other functions facilitate everyday work: For example, the pre-TARE function, with which the weight for shoes and clothing is stored and deducted with each measurement. Or the three-stage damping system that filters out patient movements.

Capacity	660 lbs / 300 kg
Graduation	0.1 lb < 330 lbs > 0.2 lb / 50 g < 150 kg > 100 g
Dimensions (WxHxD)	14.2 x 36.6 x 20.5 in / 360 x 930 x 520 mm
Platform (WxHxD)	13.2 x 3.1 x 13.6 in / 335 x 80 x 345 mm
Net weight	33.5 lbs / 15.2 kg
Power supply	Batteries, Power adapter (optional)
Functions	TARE, Pre-TARE, HOLD, Auto-HOLD, BMI, Auto-CLEAR, RESET, Automatic switch-off, lbs/kg switch-over, Adjustable damping, Mother+child function, SEND/Auto-SEND
Interfaces	Wi-Fi / Ethernet optional with seca 452
Accessories	+ Telescopic measuring rod seca 220 + Switch-mode power adapter seca 400 + Interface module seca 452 + Panda seca 459 (cannot be mounted in conjunction with height rod seca 220)

### Telescopic measuring rod seca 220 (included)

Measuring range	24 – 78 in / 60 – 200 cm
Graduation	1/8 in / 1 mm



### seca integration solutions: How to significantly improve workflows

EMR-validation means that the seca 703 can be integrated into the hospital information system via the network. In this way, measured data can be sent directly to the digital patient file (EMR) at the touch of a button, where they are immediately available to all users. An additional USB barcode scanner is also used to document who measured whom and when (patient and user identification). This saves you time, increases process reliability and eliminates transmission errors.

More information on seca integration solutions can be found at: [integration.seca.com](http://integration.seca.com)

We reserve the right to make modifications.

seca north america | west  
13601 Benson Avenue  
Chino, CA 91710  
USA

seca north america | east  
1439 Stuart Engals Blvd, Suite 200  
Mount Pleasant, SC 29464  
USA

T +1 800 542 7322  
F +1 888 705 7397  
E [info.us@seca.com](mailto:info.us@seca.com)

Precision for health  
[seca.com](http://seca.com)

5/2023